



公差等级/General	Tolerances(mm)											公差等级/General	
0	>.3	>.6	>.10	>.18	>.30	>.50	>.80	>.120	>.180	>.280	>.315	>.400	0.1/1.0
~	~	~	~	~	~	~	~	~	~	~	~	~	±Z
3	6	10	18	30	50	80	120	180	250	315	400	500	
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

REV	ECN	DESCRIPTION	DRAFT	DATE	SIZE: A4	TYPE: CUSTOMER DRAWING	SCALE: 4:1	REV	T0
1	2	3	4	5	6	1/1			
MATERIAL: /					SURFACE: /				
MAT NO.: /					NAME: DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD				
STATUS: /					DRAWING NO.: /				
APPD: /					DRAFT: WangY1 2020.05.29				
CHKD: /					8EDGVC-2.5-XP-11-01A(H)				
REV					SHEET				
1					1/1				

2	Pin	Copper alloy	Sn Plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准 /UL Standard:	B	C	D
额定电压/电压 /Rated Voltage(V)/Current(A)	150/4	150/4	150/4
IEC 标准 /IEC Standard:	过压类别 /Overvoltage Category /标称等		
污染等级 /Pollution Degree	III/3	III/2	II/2
额定电压/电压 /Rated Voltage(V)/Current(A)	130/6	/	/
额定脉冲电压(KV) /Rate Impulse Voltage(KV)	2.5	/	/
间距 /Pitch (mm) /线数/极数 /Poles	2.50	N=02~12P	
使用温度范围 /Operating Temperature(°C)	-40~+105		
符合RoHS环保要求 /Conform to RoHS	Yes		
标准颜色编号 /Standard color number:	PANTONE 428C		
PANTONE / RAL	PANTONE 428C		