

## Aperçu

### informations sur le produit



### ES-K-350-10090000081

Panel feed-through connectors for energy storage systems, rated current: 350A, rated voltage: 1000V, max cross section: 95mm², copper busbars: 20mm\*5mm, color: orange, contact surface: Ni

### Les avantages des produits

- ☒ The rotatable cover can effectively avoid the loss or damage of the cover at the construction site
- ☒ The pre cut structure can be flexibly removed according to the site conditions to enhance safety protection;
- ☒ The design of two-way opening can connect the energy storage battery in series or in parallel
- ☒ The product has low temperature rise to realize safe, economical and efficient connection

### Les certificats des produits

## Caractéristiques techniques

### Dessin de produit

### Modèle 3D

□

### Item properties

|                      |                  |
|----------------------|------------------|
| Type of installation | panel            |
| Connection method    | Screw connection |
| Number of potentials | 1                |
| Pluggable or not     | no               |

### Material data

|                             |                           |
|-----------------------------|---------------------------|
| Environmental items         | Compliant with REACH/RoHS |
| Contact material            | copper                    |
| Contact point metal surface | Nickel plating            |
| Contact zone metal surface  | Nickel plating            |

|                                 |             |
|---------------------------------|-------------|
| Insulation Materials            | PC          |
| Flammability rating             | UL94V-0     |
| Mechanical tests                |             |
| Test Specification              | UL1059      |
| Environmental data              |             |
| Ambient temperature (operation) | -40°C~125°C |

#### Accessoires

#### Caractéristiques commerciales

|                                     |             |
|-------------------------------------|-------------|
| Numéro de la commande               | 10090000081 |
| Unité d'emballage                   | 16          |
| Quantité minimale de commande       |             |
| Le poid de produit (sans emballage) | 133.8       |